

## **SECTION 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

Wunda Automotive Products Pty Ltd Factory 8, 1 Box Road		Phone: 02 9525 4228
		Fax: 02 9525 4229
Taren Point, NSW	2229	sales@wunda.net.au
Chemical nature:	Blend of ingredients.	
Trade Name:	Wunda Carb-Off Engine Cleaner	
Part Number:	WDC	
Product Use:	Carbon remover and paint stripper.	
Creation Date:	March, 2013	
This version issued:	March, 2018 and is valid for 5 years from this date.	
Poisons Information Centre: Phone 13 1126 from anywhere in Australia		

## **SECTION 2 - HAZARD IDENTIFICATION**

### Statement of Hazardous Nature

This product is classified as: T, Toxic. C, Corrosive. Hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

#### SUSMP Classification: S6

**ADG Classification:** Class 6.1: Toxic substances. Sub Risk: Class 8: Corrosive Substances. **UN Number:** 2927, TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S.







# **GHS Signal word: DANGER**

#### HAZARD STATEMENT:

- H227: Combustible liquid.
- H301: Toxic if swallowed.
- H311: Toxic in contact with skin.
- H314: Causes severe skin burns and eye damage.
- H331: Toxic if inhaled.
- H351: Suspected of causing cancer.

#### PREVENTION

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P260: Do not breathe fumes, mists, vapours or spray.
- P262: Do not get in eyes, on skin, or on clothing.
- P264: Wash contacted areas thoroughly after handling.
- P270: Do not eat, drink or smoke when using this product.
- P271: Use only outdoors or in a well ventilated area.
- P284: Wear respiratory protection.

#### RESPONSE

- P304: If inhaled: remove from contaminated area. Apply artificial respiration if not breathing.
- P310: Immediately call a POISON CENTRE or doctor/physician.
- P330: Rinse mouth.
- P361: Remove all contaminated clothing immediately.
- P363: Wash contaminated clothing before reuse.
- P301+P310: IF SWALLOWED: Immediately call a POISON CENTRE or doctor.
- P302+P352: IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water. P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### SAFETY DATA SHEET

Issued by: Wunda Automotive Products Pty Ltd

Phone: 02 9525 4228 (office hours)

P308+P313: If exposed or concerned: Get medical advice.

P332+P313: If skin irritation occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P391: Collect spillage.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Water fog or fine spray is the preferred medium for large fires.

STORAGE

P405: Store locked up.

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: Dispose of contents and containers to landfill.

#### **Emergency Overview**

Physical Description & Colour: Brown liquid.

Odour: Phenolic odour.

**Major Health Hazards:** causes severe burns, toxic in contact with skin and if swallowed, limited evidence of a carcinogenic effect.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS				
Ingredients	CAS No	Conc,%	TWA (mg/m³)	STEL (mg/m <sup>3</sup> )
Dichloromethane	75-09-2	30-60	174	not set
Cresols	1319-77-3	10-30	22	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

### **SECTION 4 - FIRST AID MEASURES**

#### **General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

**Skin Contact:** Seek urgent medical attention. Flush contaminated area with lukewarm, gently flowing water for at least 60 minutes, by the clock. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this SDS and take their advice). Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts).

**Eye Contact:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 60 minutes, by the clock, while holding the eyelid(s) open. Neutral saline solution may be used as soon as it is available. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this SDS and take their advice). Take care not to rinse contaminated water into the unaffected eye or onto face. Call a Poisons Information Centre or a doctor urgently. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting; rinse mouth thoroughly with water and contact a Poisons Information Centre, or call a doctor at once. Give activated charcoal if instructed.

## **SECTION 5 - FIRE FIGHTING MEASURES**

**Fire and Explosion Hazards**: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is little risk of an explosion from this product if commercial quantities are involved in a fire. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is little danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is liquid-tight chemical protective clothing and breathing apparatus.

Flash point: Does not burn.

### SAFETY DATA SHEET

Issued by: Wunda Automotive Products Pty Ltd

Phone: 02 9525 4228 (office hours)

Upper Flammability Limit:	Does not burn.
Lower Flammability Limit:	Does not burn.
Autoignition temperature:	556°C
Flammability Class:	Does not burn.

### **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include Nitrile, butyl rubber. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Because of the toxicity of this product, special personal care should be taken in any cleanup operation. Because of the corrosiveness of this product, special personal care should be taken in any cleanup operation. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

### **SECTION 7 - HANDLING AND STORAGE**

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## **SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION**

The following Australian Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m³)	STEL (mg/m <sup>3</sup> )
Dichloromethane	174	not set
Cresols	22	not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems. **Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Your eyes must be completely protected from this product by splash resistant goggles with face shield. All surrounding skin areas must be covered. Emergency eye wash facilities must also be available in an area close to where this product is being used.

**Skin Protection:** Because of the dangerous nature of this product, make sure that all skin areas are completely covered by impermeable gloves, overalls, hair covering, apron and face shield. See below for suitable material types. **Protective Material Types:** We suggest that protective clothing be made from the following materials: nitrile, butyl rubber.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

#### SAFETY DATA SHEET

Issued by: Wunda Automotive Products Pty Ltd

Phone: 02 9525 4228 (office hours)

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

#### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES:

Physical Description & colour:	Brown liquid.
Odour:	Phenolic odour.
Boiling Point:	Minimum 38°C at 100kPa
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	No data.
Vapour Pressure:	50 kPa at 24°C
Vapour Density:	No data.
Specific Gravity:	1.16
Water Solubility:	Slightly soluble.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data
Autoignition temp:	556°C

#### **SECTION 10 - STABILITY AND REACTIVITY**

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Under no circumstances should the container be sealed. Keep isolated from combustible materials.

Incompatibilities: strong acids, strong oxidising agents, zinc, tin, aluminium and their alloys, alkali metals.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form hydrogen chloride gas, other compounds of chlorine. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

#### **SECTION 11 - TOXICOLOGICAL INFORMATION**

#### Local Effects: Target Organs:

There is no data to hand indicating any particular target organs.

#### **Classification of Hazardous Ingredients**

Potential Health Effects	
Cresol, All Isomers	Conc>=5%: T; R24/25; R34
Dichloromethane	Conc>=1%: Xn; R40
Ingredient	Risk Phrases

#### Potential Health Effects

#### Inhalation:

**Short Term Exposure:** Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** This product is carcinogenic by inhalation exposure.

#### Skin Contact:

**Short Term Exposure:** Available data shows that this product is toxic, but further symptoms are not available. In addition product is very corrosive to the skin. Capable of causing severe burns with deep ulceration, and can penetrate to deeper layers of skin resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure. Burns may not be immediately painful; the onset of pain may be minutes to hours.

Long Term Exposure: No data for health effects associated with long term skin exposure.

#### **Eye Contact:**

**Short Term Exposure:** This product is very corrosive to eyes. It will quickly cause severe pain, and corrosion of the eye and surrounding facial tissues. Unless exposure is immediately treated, permanent blindness and facial scarring will occur.

Long Term Exposure: No data for health effects associated with long term eye exposure.

### SAFETY DATA SHEET

Issued by: Wunda Automotive Products Pty Ltd

Phone: 02 9525 4228 (office hours)

## Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. Available data shows that this product is toxic, but further symptoms are not available. However, this product is very corrosive to the gastrointestinal tract. Capable of causing severe burns with deep ulceration, and can penetrate to deeper layers of skin resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure.

Long Term Exposure: No data for health effects associated with long term ingestion.

### Carcinogen Status:

**SWA:** Dichloromethane is classified by SWA as a Class 3 Carcinogen, possibly carcinogenic to humans. See the SWA website for further details. A web address has not been provided as addresses frequently change.

NTP: Dichloromethane is classified by NTP as reasonably anticipated to be carcinogenic to humans.

See the NTP website for further details. A web address has not been provided as addresses frequently change. **IARC:** Dichloromethane is classed 2b IARC - possibly carcinogenic to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

## SECTION 12 - ECOLOGICAL INFORMATION

Insufficient data to be sure of status.

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

**Disposal:** This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration, or landfill.

## **SECTION 14 - TRANSPORT INFORMATION**

UN Number: 2927, TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. Hazchem Code: 2X Special Provisions: 274 Limited quantities: ADG 7 specifies a Limited Quantity value of 100 ml for this class of product. Dangerous Goods Class: Class 6.1: Toxic Substances. Sub Risk: Class 8, Corrosive Substances. Packing Group: II Packing Instruction: P001, IBC02 Class 6 Toxic Substances shall not be loaded in the same vehicle or packed in the same freight container with

Class 6 Toxic Substances shall not be loaded in the same vehicle of packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids where the Flammable Liquid is nitromethane), 5.1 (Oxidising Agents where the Toxic Substances are Fire Risk Substances), 5.2 (Organic Peroxides where the Toxic Substances are Fire Risk Substances), 8 (Corrosive Substances where the Toxic Substances are cyanides and the Corrosives are acids), Foodstuffs and foodstuff empties. They may however be loaded in the same vehicle or packed in the same freight container with Classes, 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Toxic Gases), 3 (Flammable liquids, except where the flammable liquid is nitromethane), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents except where the Toxic Substances), 5.2 (Organic Peroxides except where the Toxic Substances are Fire Risk Substances), 7 (Radioactive Substances), 8 (Corrosive Substances except where the Toxic Substances are cyanides and the Corrosives are acids), 9 (Miscellaneous Dangerous Goods)

## **SECTION 15 - REGULATORY INFORMATION**

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations. The following ingredients: Dichloromethane, Cresol, are mentioned in the SUSMP.

#### **SECTION 16 - OTHER INFORMATION**

This SDS contains only safety-related information. For other data see product literature.

Acronyms:		
ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)	
AICS	Australian Inventory of Chemical Substances	
SWA	Safe Work Australia, formerly ASCC and NOHSC	
CAS number	Chemical Abstracts Service Registry Number	
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters	
IARC	International Agency for Research on Cancer	
NOS	Not otherwise specified	

## SAFETY DATA SHEET

Issued by: Wunda Automotive Products Pty Ltd

Phone: 02 9525 4228 (office hours)

NTP SUSMP UN Number	National Toxicology Program (USA) Standard for the Uniform Scheduling of Medicines & Poisons United Nations Number
PRODUCT AND HOW TO SAFE	BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD STATEMENT: INFORMATION OF THE LY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE UCT WILL BE HANDLED AND USED IN THE WORKPLACE.
	R INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS
OUR RESPONSIBILITY FOR PR TO OUR CUSTOMERS AND IS	ODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016) Copyright © Kilford & Kilford Pty Ltd, March, 2018.

http://www.kilford.com.au/ Phone (02)8321 8866