

**SECTION 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

Wunda Automotive Products Pty Ltd  
Factory 8, 1 Box Road  
Taren Point, NSW 2229

Phone: 02 9525 4228

Fax: 02 9525 4229

sales@wunda.net.au

**Chemical nature:** Blend of ingredients presented as an aerosol.  
**Trade Name:** Wunda Spray Grease / Lithium Grease  
**Part Number:** WLG  
**Product Use:** Lubricant grease.  
**Creation Date:** June, 2014  
**This version issued:** June 2019 and is valid for 5 years from this date.

**SECTION 2 - HAZARD IDENTIFICATION****Statement of Hazardous Nature**

This product is classified as: Xn, Harmful. Xi, Irritating. F, Flammable. Hazardous according to the criteria of SWA. Dangerous according to Australian Dangerous Goods (ADG) Code, IATA or IMSBC criteria.

**Risk Phrases:** R10, R66, R67, R36/38. Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Irritating to eyes and skin.

**Safety Phrases:** S16, S23, S36, S51, S62, S24/25. Keep away from sources of ignition - No smoking. Do not breathe mists. Wear suitable protective clothing. Use only in well ventilated areas. If swallowed, do not induce vomiting: seek medical advice immediately and show this SDS. Avoid contact with skin and eyes.

**SUSMP Classification:** None allocated.

**ADG Classification:** Class 2.1: Flammable gases.

**UN Number:** 1950, AEROSOLS

**GHS Signal word: DANGER****HAZARD STATEMENT:**

H223: Flammable aerosol  
H280: Contains gas under pressure; may explode if heated.  
AUH066: Repeated exposure may cause skin dryness or cracking.  
H315: Causes skin irritation.  
H320: Causes eye irritation.  
H336: May cause drowsiness or dizziness.

**PREVENTION**

P102: Keep out of reach of children.  
P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.  
P211: Do not spray on an open flame or other ignition source.  
P251: Pressurized container: Do not pierce or burn, even after use.  
P261: Avoid breathing fumes, mists, vapours or spray.  
P262: Do not get in eyes, on skin, or on clothing.  
P264: Wash contacted areas thoroughly after handling.  
P271: Use only outdoors or in a well ventilated area.  
P281: Use personal protective equipment as required.

**RESPONSE**

P312: Call a POISON CENTRE or doctor if you feel unwell.  
P362: Take off contaminated clothing and wash before reuse.  
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P302+P352: IF ON SKIN: Wash with plenty of soap and water.  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

**SAFETY DATA SHEET**



P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P372: Explosion risk in case of fire.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Water fog or fine spray is the preferred medium for large fires.

#### STORAGE

P403: Store in a well-ventilated place.

P402+P404: Store in a dry place. Store in a closed container.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C.

#### DISPOSAL

P501: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

#### Emergency Overview

**Physical Description & Colour:** Pale amber coloured liquid.

**Odour:** Hydrocarbon solvent odour.

**Major Health Hazards:** irritating to eyes and skin, repeated exposure may cause skin dryness or cracking, vapours may cause drowsiness and dizziness.

#### Potential Health Effects

##### Inhalation:

**Short Term Exposure:** High vapour pressures may cause drowsiness and dizziness. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort. Intentional misuse by deliberately concentrating and inhaling contents of aerosol containers can be harmful or fatal.

**Long Term Exposure:** Vapours may cause drowsiness and dizziness.

##### Skin Contact:

**Short Term Exposure:** Major health effect from this product is misuse of the aerosol function. If sprayed continuously on skin or in eyes, it can cause frostbite.

**Long Term Exposure:** Repeated exposure may cause skin dryness or cracking.

##### Eye Contact:

**Short Term Exposure:** If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause damage through frostbite.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

##### Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

**Long Term Exposure:** No data for health effects associated with long term ingestion.

##### Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** No significant ingredient is classified as carcinogenic by IARC.

#### SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS No	Conc, %	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Liquid hydrocarbon	8052-41-3	>60	790	not set
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	10-30	not set	not set
lithium hydroxystearate	7620-77-1	1-15	not set	not set
Alkanes, C <sub>3-4</sub>	68475-59-2	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

#### SAFETY DATA SHEET



The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

## SECTION 4 - FIRST AID MEASURES

### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

**Skin Contact:** Quickly and gently blot away excess liquid. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

**Eye Contact:** Quickly and gently blot material from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

## SECTION 5 - FIRE FIGHTING MEASURES

**Fire and Explosion Hazards:** The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** In case of fire, use carbon dioxide, dry chemical, foam, water fog. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

**Flash point:** 31°C, (liquid phase)

**Upper Flammability Limit:** Not available

**Lower Flammability Limit:** Not available

**Autoignition temperature:** No data.

**Flammability Class:** Flammable Category 3 (GHS); Flammable (AS1940)

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Accidental release:** This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

## SECTION 7 - HANDLING AND STORAGE

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

## SAFETY DATA SHEET



**Storage:** Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Do not expose to temperatures exceeding 50°C. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Liquid hydrocarbon	790	not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

**Skin Protection:** Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: PVC.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES:

<b>Physical Description &amp; colour:</b>	Pale amber coloured liquid.
<b>Odour:</b>	Hydrocarbon solvent odour.
<b>Boiling Point:</b>	Not available.
<b>Freezing/Melting Point:</b>	No specific data. Liquid at normal temperatures.
<b>Volatiles:</b>	No data.
<b>Vapour Pressure:</b>	No data.
<b>Vapour Density:</b>	No data.
<b>Specific Gravity:</b>	No data.
<b>Water Solubility:</b>	Insoluble.
<b>pH:</b>	No data.
<b>Volatility:</b>	No data.
<b>Odour Threshold:</b>	No data.
<b>Evaporation Rate:</b>	No data.
<b>Coeff Oil/water Distribution:</b>	No data.
<b>Autoignition temp:</b>	No data.

## SECTION 10 - STABILITY AND REACTIVITY

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Containers should be kept dry. Keep away from sources of sparks or ignition.

**Incompatibilities:** strong oxidising agents.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Lithium compounds. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## SAFETY DATA SHEET



## SECTION 11 - TOXICOLOGICAL INFORMATION

**Local Effects:****Target Organs:** There is no data to hand indicating any particular target organs.

## Classification of Hazardous Ingredients

**Ingredient****Risk Phrases**

No ingredient mentioned in the HSIS Database is present in this product at hazardous concentrations.

## SECTION 12 - ECOLOGICAL INFORMATION

Insufficient data to be sure of status. Expected to not be an environmental hazard.

## SECTION 13 - DISPOSAL CONSIDERATIONS

**Disposal:** Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

## SECTION 14 - TRANSPORT INFORMATION

**ADG Code:** 1950, AEROSOLS**Hazchem Code:** 2YE**Special Provisions:** 63, 190, 277**Limited quantities:** ADG 7 specifies a Limited Quantity value of 1000mL for this class of product.**Dangerous Goods Class:** Class 2.1: Flammable gases.**Packaging Group:** Not set**Packaging Method:** P003

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

## SECTION 15 - REGULATORY INFORMATION

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations.

## SECTION 16 - OTHER INFORMATION

This SDS contains only safety-related information. For other data see product literature.

**Acronyms:**

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>SWA</b>	Safe Work Australia, formerly ASCC and NOHSC
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>R-Phrase</b>	Risk Phrase
<b>SUSMP</b>	Standard for the Uniform Scheduling of Medicines & Poisons
<b>UN Number</b>	United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD STATEMENT: INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

## SAFETY DATA SHEET



**Product Name: Wunda Spray Grease / Lithium Grease**

**Page: 6 of 6**

**This revision issued: June, 2019**

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)

Copyright © Kilford & Kilford Pty Ltd, February, 2015.

<http://www.kilford.com.au/> Phone (02)9251 4532

#### **SAFETY DATA SHEET**

Issued by: Wunda Automotive Products Pty Ltd

Phone: 02 9525 4228 (office hours)

**Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)**